

# ENGINE OILS

## **HiTEC® 22520**

**4T Motorcycle Additive Package**



A differentiated and dedicated four stroke motorcycle additive package



## HiTEC® 22520 4T Motorcycle Additive Package

A differentiated and dedicated four stroke motorcycle additive package

### Key Performance Benefits

HiTEC® 22520 additive package is an advanced additive package offering improved power delivery and acceleration, specifically designed to meet the unique lubrication requirements of 4 stroke motorcycles.

HiTEC® 22520 delivers the following benefits:

- Faster and more lively engine response
- Faster and safer acceleration
- Improved fuel efficiency
- Excellent protection against wear and deposits
- A more enjoyable ride

### Product Features

Excellent, sustained friction performance throughout the oil life. Meets all JASO MA2 (T903:2016) requirements. Satisfies the engine performance requirements of the API SN/CF specifications.

- Cost-effective treat-rate
- Covers all popular motorcycle viscosity grades
- Suitable for group II and group III base oils

Delivers superior performance and acceleration compared with market leading and OEM own brand oils.

HiTEC® 22520 is formulated to meet the specific needs of motorcycle engines only.

### Typical Characteristics

Appearance:	Dark brown viscous liquid
Density at 15°C, g/ml:	0.975
Flash Point, °C (PMCC):	130 min.
Kinematic Viscosity at 100°C, mm <sup>2</sup> /s:	57
Total Base Number, mg KOH/g:	80

### Handling Information

Max Handling Temp: 70 °C  
Shelf Life: 24 months at ambient temperature

