# FUELS





The Complete Driving Experience – Multifunctional Additive Package for Diesel





## HITEC® 46003 Diesel Performance Additive



The Complete Driving Experience - Multifunctional Additive Package for Diesel

### Application

HiTEC<sup>®</sup> 46003 diesel performance additive is formulated with our latest Greenclean<sup>®</sup> detergent technology, with impressive real-world fuel economy and power improvement in combination with a significant cetane improver boost to provide the complete driving experience. Our technology can restore engine cleanliness in as little as one tank of fuel.

HiTEC<sup>®</sup> 46003 provides excellent industry test performance (CEC XUD-9 and DW-10), ensuring injectors are kept clean and free from deposits.

#### **Key Performance Benefits**

- Improved fuel economy thanks to the one-tank clean-up demonstrated in critical industry tests
- Enhanced engine power and acceleration by restoring injector and combustion performance to their designed output
- Protects engines from the formation of harmful deposits
- Protects the environment by reducing harmful CO<sub>2</sub> and NO<sub>x</sub> emissions
- Extends the life of the fuel system by preventing corrosion from occurring and causing damage
- Helps prevent unscheduled maintenance and fuel filter blocking by keeping fuel systems clean
- Maximizes tank capacity due to reduced fuel foaming
- A one to six increase in cetane number

#### **Recommended Dosage**

Depending on your performance needs, the treat rate of HiTEC<sup>®</sup> 46003 can be modified to achieve a targeted level of performance. Dosage may vary depending on base fuels. Please consult your Afton contact for further information.

#### **Typical Characteristics**


Appearance:	Clear Brown liquid
Density at 15°C, g/ml:	0.96
Flash Point, °C (PMCC):	61 min.
Pour point, °C:	<-60
Kinematic Viscosity @ 40°C, mm <sup>2</sup> /s:	3.29
Kinematic Viscosity @ -20°C, mm <sup>2</sup> /s:	21.95

#### Handling Information


Max Handling Temp: 45°C Shelf Life: 12 months ambient

© 2017. Afton Chemical Corporation is a wholly-owned subsidiary of NewMarket Corporation (NYSE:NEU). HiTEC® is a trademark of Afton Chemical Corporation. 05/17.

The information in this bulletin is, to our best knowledge, sure and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Afton Chemical Corporation and its affiliates disclaim any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.



After just a few seconds, the HiTEC<sup>®</sup> 46003 fuelled car is safely back in its own lane. The un-additized car is still in the outside lane and facing oncoming traffic.



HiTEC® 46003 removes deposits that have built up on the diesel injectors.

