

# ENGINE OILS

## **HiTEC<sup>®</sup> 8766B**

**Heavy Duty Engine Oils Additive Package**



Bespoke stand-alone additive designed for ACEA E7

## HiTEC® 8766B Heavy Duty Engine Oils Additive Package

Bespoke stand-alone additive designed for ACEA E7

### Key Performance Benefits

HiTEC® 8766B HDEO has been designed with Western European needs in mind where ACEA E7 requirements are dominating.

HiTEC® 8766B provides a number of customer benefits:

- Ultimate logistics rationalisation with NO booster for API CI-4 or API CH-4
- Base oil flexibility with Group I and Group II coverage
- Optimum soot handling and VII credit
- Outstanding performance benefits, as demonstrated in Mack T8E, Mack T12, Sequence IIIF and Volvo D12D engine tests

### Typical Characteristics

Typical Characteristics	HiTEC® 8766B
Density at 15°C, g/ml	0.969
Flash Point, °C (PMCC)	135 min.
Kinematic Viscosity at 100°C, mm²/s	140
Total Base Number, mg KOH/g	74

### Handling Information

Max Handling Temp: 70 °C

Shelf Life: 24 months at ambient temperature

### Recommended Dosage

HiTEC® 8766B	Approvals																		
14.0%	●	●	●	●	●	●	P	●	●	●	●	●	●	1	●	●	●	●	●
13.4%	●	●	●	●	●	●	P	●	●	●	●	●	●	1	●	●	●	●	●
12.7%	●	●	●	●	●	P	●	●	●	●	●	●	●	●	●	●	●	●	●

P MB package approval    1 Requires TBN Boost    ● Group I or Group II base oil    ● Group II base oil only

© 2023. Afton Chemical Corporation is a wholly-owned subsidiary of NewMarket Corporation (NYSE:NEU). HiTEC® is a trademark of Afton Chemical Corporation. 03/23.

The information in this bulletin is, to our best knowledge, sure and accurate, but all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Afton Chemical Corporation and its affiliates disclaim any liability incurred in connection with the use of these data or suggestions. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents covering any material or its use.