

DRIVELINE

## HiTEC<sup>®</sup> 3339

Multifunctional Gear Additive Package



For Use with Automotive and Industrial Gear Lubricants

## HiTEC® 3339 Multifunctional Gear Additive Package

For Use with Automotive and Industrial Gear Lubricants

### Application

HiTEC® 3339 is a new multifunctional automotive gear additive based on polysulfide EP chemistry. It is developed at competitive treat rates, with options for automotive and industrial gear lubricants applications. The exceptional performance of this package has been demonstrated in extensive laboratory and field tests.

HiTEC® 3339 is specially developed for use with Group I, Group II, Group III base oils and PAO.

### Key Performance Benefits

- Multifunctional gear additive
- Solubility into Group I, II, III base oils and PAO formulations
- Robust performance in automotive and industrial gear applications
- Enhanced corrosion protection
- Capable to blend industrial gear oils at reduced dosage
- Operational savings through inventory rationalization
- Confidence and security in a product from a family of gear additives with an extensive history of trouble-free performance worldwide

### Recommended Dosage

The typical recommended dosage for HiTEC® 3339 ranges from 1.2% wt. to 3.9% wt. to meet the following specifications: AIST 224, David Brown S1.53.101 (E), AGMA 9005-D94, API GL-4, and API GL-5. Dosage is dependent on the base stock and viscosity targets. Please contact your Afton Chemical representative for specific recommendations.

### Typical Characteristics

Appearance	Orange red liquid
Density, lbs/gal.	8.34
Viscosity @ 100°C, cSt	2.5
Flash Point, °C (PMCC)	82 min.
Specific Gravity @ 15.6/15.6°C	1.001

### Handling Information

Max Handling Temp: 80°C  
Shelf Life: 24 months @ ambient temperature