

FUELS

HiTEC[®] 4110

Multifunctional Diesel Fuel Additive



Provides Excellent Keep-clean and Clean-up Injector Performance

HiTEC® 4110 Multifunctional Diesel Fuel Additive

Provides Excellent Keep-clean and Clean-up Injector Performance

Application

HiTEC® 4110 is a multi-functional diesel fuel or gas oil additive package, which boosts performance in the key areas of injector detergency, fuel economy, smoke reduction, fuel stability and corrosion protection.

Key Performance Benefits

- Excellent keep clean and clean up injector performance resulting in reduced environmental emissions, extended maintenance intervals and improved fuel economy
- Improved resistance to storage tank and fuel tank corrosion

Recommended Dosage

A dosage of 132-285 ppm by volume, (42-90 PTB) is recommended. HiTEC® 4110 has demonstrated passing Cummins L-10 performance in Cat 1K reference fuel at 142 ppm, volume (45 PTB), meeting the detergency requirements of the National Council of Weights and Measures premium diesel specifications. The higher dosage provides full performance benefits. Please contact your Afton Chemical representative for specific recommendations.

Typical Characteristics

Appearance	Clear dark amber liquid
Specific Gravity @ 15.6/15.6°C	0.904
Density, lbs/gal.	7.53
Viscosity @ 40° C, cSt	8.0
Flash Point, °C (PMCC)	39 min.

Handling Information

Max Handling Temp: 38°C
Shelf Life: 36 months @ ambient temperature

