

FUELS

# HiTEC<sup>®</sup> 4694R

Diesel Performance Additive



Bringing a New Level of Performance to Diesel Fuel

 **Afton**<sup>®</sup>  
CHEMICAL  
Passion for Solutions<sup>®</sup>

# HiTEC® 4694R Diesel Performance Additive

Bringing a New Level of Performance to Diesel Fuel



## Key Performance Benefits

HiTEC® 4694R diesel performance additive uses our latest Greenclean™2 detergent technology. This new technology has all the great performance of the previous generation but, gives enhanced clean-up at even lower treat rates. Regardless of the engine type, this new and advanced technology will restore engine cleanliness in as little as one tank of fuel.

With every tankful of fuel, Greenclean™2 HiTEC® 4694R delivers rapid, robust clean-up providing:

Full performance restoration, delivering:

- Enhanced power and acceleration
- Improved fuel economy

Protection against real-world vehicle failures:

- Filters and injectors are cleaned and maintained
- Providing peace of mind for trouble free operation

Other benefits include:

- Reduced emissions
- Enhanced engine life
- Excellent corrosion protection
- Superb anti-foam performance in biodiesel blends
- Biodiesel performance up to B10

## Recommended Dosage

The treat rate of HiTEC® 4694R additive can be modified to achieve the performance tier that you are targeting, from Economic “Keep-clean”, through to Regular “Clean-up” to Premium “Clean-up”. Treat rates may vary depending on base fuels.

## Typical Characteristics

Appearance:	Light amber liquid
Density at 15°C, g/ml:	0.907
Flash point, PMCC, °C:	>56
Kinematic viscosity at 40°C, mm <sup>2</sup> /s:	4.8
Kinematic viscosity at -20°C, mm <sup>2</sup> /s:	29

## Handling Information

Max Handling Temp: Ambient temperature  
Shelf Life: 18 months at ambient temperature

