

FUELS

## HiTEC<sup>®</sup> 6431

Aftermarket Gasoline Performance Additive



For Use in Prevention and Removal of Intake System Deposits

 **Afton<sup>®</sup>**  
CHEMICAL  
Passion for Solutions<sup>®</sup>

## HiTEC® 6431 Aftermarket Gasoline Performance Additive

For Use in Prevention and Removal of Intake System Deposits

### Application

HiTEC® 6431 gasoline performance additive is specifically formulated for use as an aftermarket fuel treatment additive for prevention and removal of intake system deposits. HiTEC® 6431 is formulated with a synthetic carrier fluid and Afton Chemical's unique Mannich detergent.

### Key Performance Benefits

- Carburetor keep clean and clean up
- Fuel injector keep clean and clean up
- Intake valve deposit keep clean and clean up
- Octane requirement increase (ORI) control
- Corrosion protection

### Recommended Dosage

Depending on your performance needs, the treat rate of HiTEC® 6431 can be modified to achieve a targeted level of performance. Please consult your Afton Chemical representative for further information.

### Typical Characteristics

|                                |                     |
|--------------------------------|---------------------|
| Appearance                     | Light yellow liquid |
| Specific Gravity @ 15.6/15.6°C | 0.9229              |
| Density, lbs/gal.              | 7.69                |
| Flash Point, °C (PMCC)         | 44 min.             |
| Pour Point, °C                 | -36 max.            |
| Viscosity @ 40°C, cSt          | 17                  |

### Handling Information

Max Handling Temp: 39°C  
Shelf Life: 40 months @ ambient temperature