

DRIVELINE

AB6

Automotive Gear Oil Additive Booster



Multifunctional Axcel Booster (AB)

AB6 Automotive Gear Oil Additive Booster

Multifunctional Axcel Booster (AB)



Key Performance Benefits

AB6 additive booster as part of the Axcel® family of additives. AB6 boosts Axcel® S to HiTEC® 343, a multifunctional gear oil additive that delivers:

- Automotive and Industrial performance
- Cost savings at all treats
- Unique MAN and ZF approval - MAN 342 M2 (160,000km), ZF TE-ML 12E (bus axles)
- Inventory control through it's multifunctionality

Recommended Dosage

The recommended dosage for AB6 additive is 0.6% wt. as a booster to Axcel® S to give HiTEC® 343 additive.

Typical Characteristics

Appearance:	Clear Yellow liquid
Density at 15°C, g/ml:	0.964
Flash Point (PMC), °C:	85
Kinematic viscosity at 40°C, mm ² /s:	20

Handling Information

Max Handling Temp: 65°C
Shelf Life: 24 months @ ambient

Axcel® Family Benefits

The new Axcel® family of core and additive boosters offers:

- Top treats to a range of applications at competitive treat-rates
- Reduced inventory control
- Improved plant utilisation
- Flexibility to meet peak demand
- Security and confidence from a product in a family of gear additives with an extensive history of trouble-free performance worldwide

