

DRIVELINE

## HiTEC<sup>®</sup> 306

Multi-functional Gear Oil Additive Package



Economic Tier, Low Treat. For Axles, Transmissions and Industrial Use

## HiTEC® 306 Multi-functional Gear Oil Additive Package

Economic Tier, Low Treat. For Axles, Transmissions and Industrial Use

Getting into Gear™ 

### Key Performance Benefits

HiTEC® 306 additive is an economical multi-functional gear oil additive that has been developed for formulating GL-5 automotive hypoid axle lubricants, GL-4 transmission lubricants and industrial gear oils.

HiTEC® 306 gear oil additive provides:

- Performance in both automotive and industrial applications
- Cost savings at all treats
- Improved inventory control
- Security and confidence from a product developed from a core chemistry with an extensive history of trouble-free performance worldwide

### Recommended Dosage

Automotive	
3.8% wt.	API GL-5 (eqv. MIL-L-2105D)
1.5% wt.	API GL-4
Industrial	
1.3% wt.	USS 224, David Brown S1.53.101(E) AGMA 9005-E02

Treat-rates may vary depending on base stock.

### Typical Characteristics

Appearance:	Clear yellow liquid
Density @ 15°C, g/ml:	1.099
Flash Point, °C (PMCC):	76 min.
Kinematic Viscosity @ 100°C, mm <sup>2</sup> /s:	9

### Handling Information

Max Handling Temp: 65°C  
 Shelf Life: 24 months @ ambient  
 6 months @ 40°C