

ENGINE OILS

HiTEC[®] 2235

Two-Stroke Additive Package



For Air-cooled Two-stroke Engine Oils

HiTEC® 2235 Two-Stroke Additive Package

For Air-cooled Two-stroke Engine Oils

Application

HiTEC® 2235 is a low-ash multifunctional additive for air cooled two-stroke engine oils. HiTEC® 2235 has been developed to meet the performance requirements including JASO FC, API-TC, ISO EGC & EGD and Thailand Industrial Standards Institute (T.I.S.I. 1040).

Key Performance Benefits

- Strong detergent performance
- Increased protection from piston seizure, ring sticking, engine deposits and exhaust blocking
- Ability to be used with a wide variety of basestock systems

Recommended Dosage

Recommended dosages for HiTEC® 2235 ranges between 3.0% wt. to 7.5% wt., though dosage is dependent on base stock and viscosity targets. Please contact your Afton Chemical representative for specific recommendations.

Typical Characteristics

Appearance	Dark brown viscous liquid
Density, lbs/gal.	7.76
Viscosity @ 100°C, cSt	170
Flash Point, °C (PMCC)	135 min.
TBN, mg KOH/g	44
Specific Gravity @ 15.6/15.6°C	0.935

Handling Information

Max Handling Temp (<24 hrs): 70°C

Shelf Life: 36 months @ ambient (10-30°C)