

FUELS

HiTEC[®] 18130N

Winter Diesel Fuel Additive

Formulated with Cold Flow Technology



Provides Exceptional Winter Performance in #2 Diesel

 **Afton[®]**
CHEMICAL
Passion for Solutions™

HiTEC® 18130N Winter Diesel Fuel Additive

Provides Exceptional Winter Performance in #2 Diesel

Application

HiTEC® 18130N winter diesel fuel additive is a concentrated, heavy-duty, diesel fuel additive for winter use, designed for adequate fluidity when stored above -30°F. It is formulated with a proprietary blend of components that delivers superior CFPP performance, improved low temperature handling and excellent wax anti-settling performance. It does not contain deicer. HiTEC® 18130N is specially formulated to provide exceptional winter performance in #2 diesel.

HiTEC® 18130N is safe for use in heavy duty, diesel powered equipment for on-road, off-road and marine use. It should be added to the storage tank prior to each delivery to ensure a homogeneous additive/fuel mixture. As with any fuel additive, exercise care by handling HiTEC® 18130N in well ventilated areas while wearing proper eye and skin protection. Refer to MSDS for more specific information.

Key Performance Benefits

- Improves low temperature operability in a wide range of fuels by lowering the CFPP (cold filter plugging point) and pour point without reducing the fuel's energy content

Recommended Dosage

HiTEC® 18130N is recommended for use at 1 gallon per 3,000 gallons of #2 diesel. This product has been specially formulated for use in today's modern diesel fuels and typical biodiesel blends. Please contact your Afton Chemical representative for specific recommendations.

Typical Characteristics

Appearance	Clear to hazy yellow amber liquid
Density, lbs/gal.	7.40
Specific Gravity @ 15.6/15.6°C	0.888
Viscosity @ 40°C	4
Flash Point, °C (C)	45 min.

Handling Information

Max Handling Temp: 40°C
Shelf Life: 24 months