

FUELS

## HiTEC<sup>®</sup> 4170AS

Refinery and Distribution Additive



Monoacid Lubricity and Conductivity Improver Additive for  
ULSD

# HiTEC® 4170AS Refinery and Distribution Additive

Monoacid Lubricity and Conductivity Improver Additive for ULSD

## Application

HiTEC® 4170AS is a monoacidic additive designed to improve the lubricity and conductivity of on-road and off-road low sulfur diesel. Formulated to deliver maximum performance at the lowest treat rates, HiTEC® 4170AS is ideal for customers located in warmer climates or those using heated storage.

## Key Performance Benefits

- Increases lubricity and electrical conductivity of diesel fuel at low treat rates
- Concentrated product eliminating excess solvent
- Low viscosity allows handling down to 0°C (32°F)
- Compatible with all commonly used diesel additives

## Recommended Dosage

Treat rates will vary depending on base fuels. Typical treat rates are suggested at 50 to 150 ppmw depending on the fuel response and target performance.

## Typical Characteristics

Appearance	Yellow liquid
Density, lbs/gal.	7.503
Specific Gravity @ 15.6°C	0.90
Flash Point, °F (PMCC)	134.6 min.
Viscosity @ 0°C, cSt	35

## Handling Information

Recommended Storage & Handling Temp: 10–40°C  
 Shelf Life: 24 months when stored as directed

