

FUELS

HiTEC[®] 46600

Multifunctional Diesel Performance Additive



Raising The Bar For Best-In-Class Performance

 **Afton**[®]
CHEMICAL
Passion for Solutions[®]

HiTEC® 46600 Multifunctional Diesel Performance Additive



Raising The Bar For Best-In-Class Performance

Application

HiTEC® 46600 diesel performance additive is formulated with Afton's latest Greenclean® detergent technology, with impressive real-world fuel economy and power improvement to provide the complete driving experience and minimize downtime. Our technology can restore engine cleanliness in as little as one tank of fuel.

HiTEC® 46600 provides excellent industry test performance (CEC XUD-9 and DW-10), ensuring injectors are kept clean and free from deposits.

Key Performance Benefits

- Improved fuel economy thanks to the one-tank clean-up demonstrated in critical industry tests, and impressive fuel economy recovery demonstrated in real world conditions
- Enhanced engine power and acceleration by restoring injector and combustion performance to their designed output
- Protects engines and injectors from the formation of harmful deposits
- Protects the environment by reducing harmful CO₂ and NO_x emissions
- Extends the life of the fuel system by preventing corrosion from occurring and causing damage
- Helps prevent unscheduled maintenance, fuel filter blocking, and DPF regeneration by keeping fuel systems clean
- Reduces the tendency of low sulphur fuels to static electricity discharge, by improving the conductivity of the treated fuel

Recommended Dosage

Depending on your performance needs, the treat rate of HiTEC® 46600 can be modified to achieve a targeted level of performance. Dosage may vary depending on base fuels. Please consult your Afton contact for further information.

Typical Characteristics

Appearance	Amber Liquid
Density @ 15°C, lbs/gal	7.57
Viscosity @ 40°C, cSt	5
Flash Point, °C (PMCC)	56 min.

Handling Information

Max Handling Temp: 40°C
Shelf Life: 18 months @ ambient

