

FUELS

HiTEC[®] 46602

Multifunctional Diesel Performance Additive



Raising The Bar For Best-In-Class Performance

 **Afton[®]**
CHEMICAL
Passion for Solutions[®]

HiTEC® 46602 Multifunctional Diesel Performance Additive



Raising The Bar For Best-In-Class Performance

Application

HiTEC® 46602 Diesel Performance Additive is formulated with Afton's latest Greenclean® detergent technology to remove sticky internal injector deposits and prevent wear. With impressive real-world fuel economy recovery, power improvement, less downtime, and lower maintenance costs, HiTEC® 46602 provides the complete driving experience.

Key Performance Benefits

- Improved fuel economy thanks to the one-tank clean-up demonstrated in critical industry tests, and impressive fuel economy recovery demonstrated in real world conditions
- Enhanced engine power and acceleration by restoring injector and combustion performance to their designed output
- Protects engines and injectors from the formation of harmful deposits
- Protects the environment by reducing harmful CO₂ and NO_x emissions
- Extends the life of the fuel system and injector parts by improving fuel lubricity and preventing corrosion
- Helps prevent unscheduled maintenance, fuel filter blocking, and DPF regeneration by keeping fuel systems clean
- Reduces the tendency of low sulphur fuels to static electricity discharge, by improving the conductivity of the treated fuel

Recommended Dosage

Depending on your performance needs, the treat rate of HiTEC® 46602 can be modified to achieve a targeted level of performance. Dosage may vary depending on base fuels. Please contact your Afton contact for further information.

Typical Characteristics

Appearance	Amber Liquid
Density @ 15.6°C, lbs/gal	7.54
Specific Gravity @ 15.6/15.6°C	0.9040
Viscosity @ 40°C, mm ² /s	7.9
Flash Point, °C (PMCC)	41 min.

Handling Information

Max Handling Temp: 40°C
Shelf Life: 24 months @ ambient

